PREMIUM+ PDU WITH RACKLINK™, RLNK-P915R-SP, 9 OUTLET, 15A, SERIES PROTECTION™ SURGE

RLNK-P915R-SP |

FEATURES & BENEFITS

More than power distribution, the Premium+ PDU with RackLink™ is the most advanced - yet simplest - to use IP control solution for Remote System Management in the industry. Developed around a platform that has been proven on the most secure networks in the world, this next-generation power distribution unit provides unmatched monitoring, control, logging, security and power protection capabilities available for demanding AV applications. The RackLink™ technology allows you to control locally or virtually through 3rd party AV control systems, cloud platforms and SNMP for flexible management that is smarter, faster and reduces service costs.

- Simple system setup with advanced capabilities
  - Save programming with integrated scheduling, variable timed sequencing, ping sequencing, auto healing, thresholds, and multiple notification options.
  - Easily connect to control and IT systems with universal compatibility through custom drivers, SNMP v3/MIB, RESTful API, and 3rd party integrations.
  - Connecting via Wi-Fi with a 3rd party dongle dramatically reduces the number of Ethernet ports required
  - Configure one PDU or a thousand PDUs in a matter of moments with the ability to save your configuration files
  - Remotely update firmware without having to shut down the PDU, ensuring consistent system uptime
- Best-in-class monitoring, logging, and data reporting for remote system management with a user-friendly interface.
  - Superior metering accuracy of total power draw down to outlet level including current, voltage, power, power factor and energy usage
  - Patent-pending IP sequencing sets user-defined delays and establishes that an IP device will not power on until its networked companion is powered on
  - Connect up to 32 environmental sensors to monitor the temperature and humidity and alert potential threats that could cause system downtime
- Industry-leading network security and support of IT protocols for demanding end users
  - SSL/TLS Certificates
  - SSH
  - HTTPS

- Self-signed certificates
- Protect valuable AV equipment with patented Series Protection™; safeguarding critical systems against:
  - Surge
  - Over voltage
  - Under voltage
  - Noise
- Built in partnership with Raritan, a leader in the growing intelligent power market, using their Xerus platform to deliver robust security features and intelligence
- Compliant with AVIXA Energy Management Standard to support energy efficient AV system design, monitoring and optimization.

SPECIFICATIONS

GENERAL INFO

Surge Protected: Series Protection

TECHNICAL INFORMATION

AC Voltage Output: 12A
AC Voltage Input: 80-140VAC 60/50Hz
Amps: 15 Amps
Current Max: 120VAC 15A
Firmware Update: Yes - See Resources
Graphical User Interfaces: RackLink™ Dashboard
LAN Ports: Yes
Max Surge Current: Unlimited
Mounting: Horizontal
Patent No: US 8,947,844
Receptacle Type: NEMA 5-15R
Surge Suppression: Series Protection