

ZU607TST

High brightness short throw laser projector



- **Bright short throw WUXGA laser projector - 6000 lumens**
- **30,000 hours maintenance-free laser light source at full brightness**
- **4K, HDR and HLG compatibility**
- **HDBaseT 3.0 connectivity**

At 6000 lumens, with 4K and HDR compatibility, the ZU607TST features a dust resistant IP6X certified optical engine for 24/7 operational capabilities and low maintenance. The ZU607TST short throw projector features extremely long-life laser technology, manual horizontal and vertical lens shift and built-in 15W speakers.



Specifications

UPC: 796435 44 675 8, EAN: 5055387667594, Colour: Black



| | |
|---------------------------------------|--|
| Display/image | |
| Display technology | DLP |
| Resolution | WUXGA (1920x1200) |
| Brightness | 6,000 lumens |
| Contrast ratio | 300,000:1 |
| Native aspect ratio | 16:10 |
| Aspect ratio - compatible | 4:3,16:9,16:10 |
| Keystone correction - horizontal | +/-15° |
| Keystone correction - vertical | +/-15° |
| Has vertical auto keystone correction | Yes |
| Displayable colors (millions) | 1073.4 |
| Horizontal scan rate | 5~140HzKhz |
| Vertical scan rate | 24~120HzHz |
| Uniformity | 85% |
| Screen size | 30" ~ 300" diagonal |
| Lamp info | |
| Light source type | Laser |
| LASER life | 30,000 hours |
| Optical | |
| Throw ratio | 0.58:1 |
| Projection distance | 14.96" - 147.64" |
| Zoom type | Fixed |
| Focal length (mm) | 8.51 |
| Lens shift | Vertical -100 ~ 110%, Horizontal: +/-4% |
| Native offset | 110% |
| Lens shift | Yes - {{downloads_link}} |
| Connectivity | |
| Connections | Inputs 2 x HDMI 2.0, 2 x VGA, 1 x Composite video, 2 x Audio 3.5mm, 1 x USB-A power 1.5A Outputs 1 x HDMI 2.0, 1 x Audio 3.5mm, 1 x 3D sync, 1 x 12V trigger Control 1 x HDBaseT 4K, 1 x RJ45, 1 x RS232 |
| LAN - wireless networking | No |
| General | |
| Noise level (min) | 33dB |
| Noise level (max) | 36dB |
| 3D | Full 3D |
| Security | Security bar, Kensington Lock, Password protected interface |
| IP rating | IP6X |
| OSD / display languages | 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| 360° operation | Yes |
| Remote control | Backlit ProAV remote |
| Speaker count | 2 |
| Watts per speaker | 15W |
| In the box | AC power cord Remote control 2x AAA batteries Basic user manual |
| Networking | |
| LAN - control | Yes |
| LAN - wireless networking | No |
| LAN | Yes |
| Power | |
| Power supply | Universal AC 100--240V± 10%~ 50 / 60 Hz with PFC input |
| Power consumption (standby) | <0.5W |
| Power consumption (min) | 240W |
| Power consumption (max) | 366W |
| Weight and dimensions | |
| Dimensions (W x D x H) | 14.72" x 11.89" x 4.61" |
| Gross weight | 18.96 lbs |
| Net weight | 13.89 lbs |

